



## TR300

### Temperature and Relative Humidity Data Logger

The Amprobe TR300 temperature and humidity data logger is designed to monitor indoor air quality in one compact size unit. The housing includes a wall-mount hook for easy installation. It has a large digital triple display and audible and visible alarms. Plus a fast responding sensor and electronics to help monitor the relative humidity and temperature of the indoor air.

The TR300 has capacity to store 16,000 readings and ships with the unique Amprobe Download Suite software. Set up these parameters for recording: Sample interval timing, Start/Stop, Date and Time, HI/LO Alarm threshold, Unit Selection and number of Memory points. Download Suite software works with all Amprobe devices and stores the data from the TR300 for further analysis.

### No hassle warranty

*No waiting.*

*No shipping charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSRP limit)

- Instrument for indoor air quality monitoring
- Temperature / RH in one model
- Wall mountable, self-standing or tripod mountable
- Extra large digital display
- Displays Temperature, RH plus Real time date/hour stamp
- Air Temperature or Dew Point (DP) display and Celsius/ Fahrenheit are selectable
- Offers both visible LEDs plus audible warnings to monitor IAQ condition
- Small size design with USB interface
- Memory points selection : 1000, 2000, 4000, 6000, 8000,12000,16000
- Includes USB Cable, Amprobe's Download Suite Software CD, Table Feet, User Manual, Batteries



## TR300 Temperature and Relative Humidity Data Logger

## Data Sheet

### Specifications

<b>General</b>		
<b>Range</b>	Relative Humidity Temperature	0 to 100% -20 to 70°C (-4 to 158°F)
<b>Accuracy</b>	Relative Humidity Temperature	±3% @ 10~90%; ±5% @ others ±0.6°C (±1°F) @ 0~50°C (32°F~122°F); ±1.2°C (±2°F) @ others
<b>Resolution</b>	Temperature Humidity	0.1°C/ 0.1°F 0.1%
<b>Battery Life</b>	150 Hours	
<b>Electrical</b>		
<b>Battery</b>	4 ea AA batteries included	
<b>Mechanical</b>		
<b>Dimension</b>	175 x 42 x 16 mm (6.89 x 1.65 x 0.63 in)	
<b>Weight</b>	0.282 Kg (0.622 lb)	
<b>Case</b>	N/A	
<b>Environmental</b>		
<b>Operating Humidity</b>	0-100% RH	
<b>Operating Temperature</b>	-20 to 70°C (-4 to 158°F)	
<b>Storage Temperature</b>	-20 to 70°C (-4 to 158°F)	
<b>Agency Approvals &amp; Certifications</b>	CE	

**Amprobe® Test Tools**  
website: [www.Amprobe.com](http://www.Amprobe.com)  
email: [info@amprobe.com](mailto:info@amprobe.com)  
Everett, WA 98203  
Tel: 877-AMPROBE

**Amprobe® Test Tools Europe**  
Amprobe Test Tools Europe  
Beha-Amprobe GmbH  
In den Engematten 14  
79286 Glottertal, Germany  
Tel.: +49 (0) 7684 8009 - 0

©2008 Amprobe Test Tools. All rights reserved.  
7/2008 3358086 Rev A