




DSG3000 Series RF Signal Generator

- The highest frequency: 3 GHz/6 GHz
- Amplitude accuracy: <0.5dB (typical)
- Output amplitude range: -130 dBm to +13 dBm
- High signal purity, phase noise: <-110dBc/Hz@20kHz (typical)
- Standard 0.5ppm internal clock; 5ppb high stable clock for option
- Standard AM/FM/ΦM analog modulation
- Standard pulse modulation; on/off ratio up to 80dB; pulse train generator for option
- I/Q modulation and I/Q baseband output
- All modulations support internal and external modulation modes
- Standard 2U height design to save rack space; rack mount kit is available
- Standard USB/LAN/GPIB remote control interfaces; support SCPI command set
- Wear-free electronic attenuator design
- Well-designed automatically flatness calibration function (Cables, attenuators, amplifiers and so on) for test system with power meter control




DSG3000 Series RF Signal Generator



Dimensions: W × H × D = 364 mm × 112 mm × 420 mm; Weight: 6.4kg (without packaging)

► Main Functions



► Specifications

Specifications are valid under the following conditions: the instrument in the calibration cycle is stored at least two hours at 0°C to 50°C temperature, and 40 minutes warm up. The specifications include measurement uncertainty. Data represented in this manual are specifications unless otherwise noted.

Typical (typ.): describes characteristic performance, which 80 percent of the measurement results will meet at room temperature (approximately 25 °C). This data is not warranted, does not include measurement uncertainty.

Nominal (nom.): indicates the expected mean or average performance, or an attribute whose performance is by design, such as the 50Ω connector. This data is not warranted and is measured at room temperature (approximately 25 °C).

Measured (meas.): describes an attribute measured during the design phase for purposes of communicating expected performance, such as amplitude drift vs. time. This data is not warranted and is measured at room temperature (approximately 25 °C).

NOTE: All charts represented in this manual are the measurement results of multiple instruments at room temperature unless otherwise noted.

Frequency

Frequency		
Frequency range	DSG3030	9kHz ~ 3GHz
	DSG3060	9kHz ~ 6GHz
Frequency resolution	0.01Hz	
Frequency switching speed	<10ms ^[1] (typ.)	
Phase offset	Adjustable in 0.01° steps (nom.)	

Frequency Bands ^[2]		
Band	Frequency	N
1	f ≤ 23.4375MHz	1
2	23.4375MHz < f ≤ 46.875MHz	0.03125
3	46.875MHz < f ≤ 93.75MHz	0.0625
4	93.75MHz < f ≤ 187.5MHz	0.125
5	187.5MHz < f ≤ 375MHz	0.25
6	375MHz < f ≤ 750MHz	0.5
7	750MHz < f ≤ 1500MHz	1
8	1500MHz < f ≤ 3000MHz	2
9	3000MHz < f ≤ 6000MHz	4



Internal Reference Frequency		
Reference frequency	10MHz	
Temperature stability	In temperature range 0°C to 50°C , reference to 25°C	< 0.5ppm
	With OCXO-A08 option	< 5ppb
Aging rate		< 1ppm/year
	With OCXO-A08 option	< 30ppb/year
Output for internal reference frequency	Frequency	10MHz
	Level	+8dBm (typ.)
	Output impedance	50Ω (nom.)
Input for external reference frequency	Frequency	10MHz
	Level	0dBm to +10dBm
	Maximum deviation	±5ppm
	Input impedance	50Ω (nom.)

Frequency Sweep		
Operating modes	Step sweep (equally or logarithmically spaced frequency steps) List sweep (the list of arbitrary frequency steps)	
Sweep modes	Single, continuous	
Sweep range	Full frequency range	
Sweep shapes	Triangle, ramp	
Step change	Linear or logarithmic	
Number of points	Step sweep	2 to 65535
	List sweep	1 to 6001
Dwell time range	20ms to 100s	
Triggering	Auto, trigger key, external, bus (GPIB, USB, LAN)	

NOTE: [1] Except in the case of the band1 is switched with the other band.

[2] N is a factor used to help define certain specifications within the document.


Spectral Purity ^[1]		
Harmonics	CW mode, 1MHz $\leq f \leq$ 6GHz, level $\leq +13$ dBm	<-30dBc
Sub harmonics	CW mode $f \leq 3$ GHz 3 GHz $< f \leq 6$ GHz	<-65dBc, <-80dBc (typ.) <-52dBc, <-70dBc (typ.)
Non harmonics	CW mode, level > -10 dBm, carrier offset > 10 kHz $f \leq 1.5$ GHz 1.5 GHz $< f \leq 3$ GHz 3 GHz $< f \leq 6$ GHz	<-64dBc, <-70dBc (typ.) <-58dBc, <-64dBc (typ.) <-52dBc, <-58dBc (typ.)
SSB phase noise	CW mode, at 20kHz carrier offset, 1Hz measurement bandwidth $f = 100$ MHz $f = 1$ GHz $f = 3$ GHz $f = 6$ GHz	<-120dBc/Hz <-108dBc/Hz, <-110dBc/Hz (typ.) <-102dBc/Hz, <-104dBc/Hz (typ.) <-96dBc/Hz, <-98dBc/Hz (typ.)
Residual FM	CW mode, RMS value at $f = 1$ GHz 0.3kHz to 3kHz 0.03kHz to 20kHz	<5Hz rms, <1Hz rms (typ.) <30Hz rms, <8Hz rms (typ.)



NOTE: [1] Without IQ-DSG3000 option.

Level

Setting Range		Specification level range	Setting range
Maximum output level	9kHz ≤ f <100kHz	+7dBm	+10dBm
	100kHz ≤ f <1MHz	+13dBm	+15dBm
	1MHz ≤ f ≤3GHz	+13dBm	+25dBm
	3GHz <f ≤6GHz	+13dBm	+20dBm
Minimum output level	9kHz ≤ f <100kHz	-110dBm	-120dBm
	100kHz ≤ f ≤ 6GHz	-130dBm	-140dBm
Setting resolution	0.01dB		




Absolute Level Uncertainty^[1]

Level uncertainty	9kHz ≤ f <100kHz	+13 ~ -60dBm	-60 ~ -110dBm	-110 ~ -130dBm
	100kHz ≤ f ≤3GHz	≤ 0.5dB (typ.)	≤ 0.7dB (typ.)	
	3GHz <f ≤6GHz	≤ 0.7dB, ≤0.5 (typ.)	≤0.9dB, ≤0.5 (typ.)	≤0.7dB (typ.)
VSWR ^[2]	1MHz ≤ f ≤6GHz	<1.8 (typ.)		≤0.9dB (typ.)


NOTE: [1] ALC state: on or auto mode, 20°C to 30°C

[2] In 50Ω system, typical, level ≤-10dBm, ATT auto mode


Measured +13dBm output level VS frequency




Measured 0dBm output level VS frequency




Measured -60dBm output level VS frequency




Measured -110dBm output level VS frequency



Measured -127dBm output level VS frequency



Measured -136dBm output level VS frequency



Level Setting		
Setting time	ALC state on, frequency fixed, temperature range: 20°C to 30°C	≤ 5ms (typ.)
Uninterrupted level setting range	ATT fixed mode, ALC state on, level range -110dBm to +13dBm	>20dB (typ.)
Max. Reverse Power		
Max. reverse Power	Max. DC voltage 1MHz < f ≤ 6GHz	50V 10W
Level Sweep		
Operating modes	Step sweep (equally spaced level steps) List sweep (the list of arbitrary level steps)	
Sweep modes	Single, continuous	
Sweep range	Full level range	
Sweep shapes	Triangle, ramp	
Step change	Linear	
Number of points	Step sweep List sweep	2 to 65535 1 to 6001
Dwell time range	20ms to 100s	
Triggering	Auto, trigger key, external, bus(GPIB, USB, LAN)	

Internal Modulation Generator (LF)

Internal Modulation Generator (LF)		
Waveforms	Sine, square, triangle, ramp, sine sweep	
Frequency range	Sine, sine sweep Square Triangle, ramp	0.1Hz to 1MHz 0.1Hz to 20kHz 0.1Hz to 100kHz
Resolution	0.01Hz	
Frequency error	Same as RF reference source	
Output voltage ^[1]	Setting range Resolution	1mV to 3V 1mV
Output impedance	50Ω (nom.)	
Sine sweep	Sweep modes Sweep range Sweep time Sweep shapes Triggering	Single, continuous Frequency range of LF output 1ms to 1000s Triangle, ramp Auto, trigger key, external, bus (GPIB, USB, LAN)

Modulation^[2]

Simultaneous Modulation					
	AM	FM	ØM	Pulse mod.	I/Q mod. (option)
AM	–	○	○	△	×
FM	○	–	×	○	○
ØM	○	×	–	○	○
Pulse mod.	△	○	○	–	○
I/Q mod.(option)	×	○	○	○	–

NOTE: ○:compatible; ×: incompatible; △:compatible with AM performance reduced


Amplitude Modulation		
Modulation source	Internal, external, internal + external	
Modulation depth ^[3]	0% to 100%	
Resolution	0.1%	
AM depth uncertainty	$f_{mod}=1\text{kHz}$	<4% of setting+1%
AM distortion	$f_{mod}=1\text{kHz}$, m<30%, level=0dBm	<3% (typ.)
Modulation frequency response	m<80%, 10Hz to 50kHz	<3dB (nom.)

NOTE: [1] Measurement in high-impedance state.

[2] The modulation source is sine waveform unless otherwise noted.

[3]Peak power of the envelope is no more than the maximum value of the specification output range.

Frequency Modulation		
Modulation source	Internal, external, internal + external	
Maximum deviation	$N \times 1\text{MHz}$ (nom.)	
Resolution	<0.1% of deviation, or 1Hz, which ever is greater (nom.)	
Setting uncertainty	$f_{\text{mod}}=1\text{kHz}$, internal mode	<2% of setting+20Hz
FM distortion	$f_{\text{mod}}=1\text{kHz}$, deviation= $N \times 50\text{kHz}$	<2% (typ.)
Modulation frequency response ^[1]	10Hz to 100kHz	<3dB (nom.)
Phase Modulation		
Modulation source	Internal, external, internal + external	
Maximum deviation	$f \leq 23.4375\text{MHz}$	3rad (nom.)
	$f > 23.4375\text{MHz}$	$N \times 5\text{rad}$ (nom.)
Resolution	<0.1% of deviation, or 0.01rad, which ever is greater, (nom.)	
Deviation accuracy	$f_{\text{mod}}=1\text{kHz}$, internal modulation source	<1% of setting+0.1rad
ØM total harmonic distortion	$f_{\text{mod}}=1\text{kHz}$, deviation=5rad	<1% (typ.)
Modulation frequency response ^[2]	10Hz to 100kHz	<3dB (nom.)
Pulse Modulation		
Modulation source	External, internal	
On/off ratio	$25\text{MHz} \leq f < 3\text{GHz}$	>80dB
	$3\text{GHz} \leq f \leq 6\text{GHz}$	>70dB
Rise/fall time (10%/90%)	<50ns ^[3] , 10ns (typ.)	
Pulse repetition frequency	DC to 1MHz	
Pulse Generator		
Operating modes	Single pulse, double pulse, pulse train(option PUG-DSG3000)	
Pulse period	Setting range	40ns to 170s
	Resolution	10ns
Pulse width	Setting range	10ns to (170s-10ns)
	Resolution	10ns
Trigger delay	Setting range	10ns to 170s
	Resolution	10ns
Double-pulse spacing	Setting range	20ns to (170s-20ns)
	Resolution	10ns
Triggering	Auto, external trigger, external gate, trigger key, bus (GPIB, USB, LAN)	
Pulse Train Generator (Option PUG-DSG3000)		
Pulse train generator	Number of pulse patterns	1 ~ 2047
	On/off time range	20ns to 170s
	Repetition per pattern	1 to 256




NOTE: [1] External operating mode, measured at 100kHz deviation.

[2] External operating mode, measured at 5rad deviation.

[3] The state of ALC is off.

I/Q Modulation (Option IQ-DSG3000)		
Modulation source	External, internal	
	External modulation	
	Baseband (I or Q)	Up to 120MHz (nom.)
Bandwidth.(RF)	RF (I + Q)	Up to 240MHz (nom.)
	Internal modulation	
	Baseband (I or Q)	Up to 30MHz (nom.)
	RF (I + Q)	Up to 60MHz (nom.)
Carrier suppression ^[1]	Carrier frequency range: $50\text{MHz} \leq f \leq 6\text{GHz}$	$\geq 40\text{dBc}$ (typ.)
Suppression of image sideband ^[2]	Modulation bandwidth up to $\pm 10\text{MHz}$	$\geq 40\text{dBc}$ (typ.)
External I/Q inputs	VSWR	<1.5
	Full scale input	$\sqrt{I^2 + Q^2} = 0.5V_{rms}$
Internal modulation		
EVM	16QAM , root cosine filter ($\alpha=0.22$), 4MSps 50MHz $\leq f \leq 3\text{GHz}$ (level $\leq 4\text{dBm}$) 3GHz $< f \leq 6\text{GHz}$ (level $\leq 0\text{dBm}$) QPSK , root cosine filter ($\alpha=0.22$), 4MSps 50MHz $\leq f \leq 3\text{GHz}$ (level $\leq 4\text{dBm}$) 3GHz $< f \leq 6\text{GHz}$ (level $\leq 0\text{dBm}$)	$\leq 0.7\%\text{rms}$ (typ.) $\leq 1.2\%\text{rms}$ (typ.) $\leq 0.7\%\text{rms}$ (typ.) $\leq 1.2\%\text{rms}$ (typ.)
External modulation		
EVM	CDMA2000/1xEV-D0, 1.2288 Mcps, frequency 800 to 900MHz, 1800 to 1900MHz, level $\leq 4\text{dBm}$	$\leq 1.2\%$, $\leq 0.8\%$ (typ.) $\geq 70\text{dB}$



NOTE: [1] [2]The parameter is measured at room temperature. When the temperature is difference from room temperature, the specification will deteriorate.

I/Q Baseband Generator (Option IQ-DSG3000)			
Output impedance	50Ω (nom.)		
Output voltage	Setting range	0.1V _{pp} to 1.5V _{pp}	
	Resolution	1mV	
Frequency response	Referenced to 1MHz	≤ 10MHz ≤ 30MHz	<0.5dB (nom.) <1dB (nom.)
	Magnitude	≤ 10MHz ≤ 30MHz	<0.1dB (nom.) <0.2dB (nom.)
I/Q imbalance	Nonlinear phase	≤ 10MHz ≤ 30MHz	200ps (nom.) 500ps (nom.)
SFDR	Sine	≤ 30MHz	>50dB (nom.)
	Waveform length		1 sample to 8 Msample in one-sample steps
Waveform memory	Resolution		14 bits
	Loading time 1Msample		<10 s ^[1] (nom.)
	Nonvolatile memory		1G Bytes
Sample rate	Setting range		1 kHz to 50 MHz, 100 MHz
	Resolution		0.01 Hz
	Triggering		Auto, trigger key, external, bus(GPIB, USB, LAN)
	Operating modes		Retrig, armed auto, armed retrig, single
Trigger	External trigger delay		
	Setting range	0 to (2 ¹⁶ - 1)	
	Resolution	1	
	External trigger inhibit		
	Setting range	0 to (2 ¹⁶ - 1)	
	Resolution	1	
	External trigger pulse width		>20 ns (nom.)

Inputs and Outputs

Front Panel Connectors		
RF output	Impedance	50Ω (nom.)
	Connector	N female
External modulation signal input	Impedance	50Ω (nom.)
	Connector	BNC female
Internal modulation generator.(LF) output	Impedance	50Ω (nom.)
	Connector	BNC female
Rear Panel Connectors		
External trigger in	Impedance	1kΩ (nom.)
	Connector	BNC female
	Trigger voltage	5V TTL level
Signal valid output	Connector	BNC female
	Output voltage	0V/3.3V (nom.)
Sweep out	Connector	BNC female
	Output voltage	0 to 10V (nom.)
Pulse input or output	Impedance	50Ω (nom.)
	Input/output voltage	0V/3.3V (nom.)
10MHz in (external frequency reference input)	Impedance	50Ω (nom.)
	Connector	BNC female
10MHz out (external frequency reference output)	Impedance	50Ω (nom.)
	Connector	BNC female
I/Q baseband input/output (option IQ-DSG3000)	Impedance	50Ω (nom.)
	Connector	BNC female

Rear Panel Communication Interface		
USB host	Connector	A plug
	Protocol	Version2.0
USB device	Connector	B plug
	Protocol	Version2.0
LAN	LXI core device 2011 class	10/100Base, RJ-45
IEC/IEEE bus (GPIB)		IEEE488.2

NOTE: [1] Load from flash internal non-volatile memory.

General Specifications

Display				
Type	TFT LCD			
Resolution	480*272			
Size	4.3"			
Mass Memory				
Mass memory	Flash non-volatile memory (internal); USB disk (not supplied)			
Data storage space	Flash non-volatile memory (internal)	1G Bytes		
Power Supply				
Input voltage range, AC	100V to 240V (nom.)			
AC supply frequency	45Hz to 440Hz			
Power consumption	With all options	50W (typ.), max. 60W		
Electromagnetic Compatibility and Safety				
EMC	In line with EN61326-1:2006			
	IEC 61000-4-2:2001	±4.0kV (contact discharge), ±4.0kV (air discharge)		
	IEC 61000-4-3:2002	3V/m (80MHz to 1GHz) 3V/m (1.4GHz to 2GHz) 1V/m (2.0GHz to 2.7GHz)		
	IEC 61000-4-4:2004	1kV power lines		
	IEC 61000-4-5:2001	0.5kV (phase to Neutral) 0.5kV (phase to PE) 1 kV (neutral to PE)		
	IEC 61000-4-6:2003	3V,0.15-80MHz		
	IEC 61000-4-11:2004	Voltage dip: 0 % UT during half cycle 0 % UT during 1 cycle 70 % UT during 25 cycles Short interruption: 0 % UT during 250 cycles		
Electrical safety	In line with UL 61010-1:2012 CAN/CSA-C22.2 No. 61010-1-12 EN 61010-1:2010			
Environmental				
Temperature	Operating temperature range	0°C to 50°C		
	Storage temperature range	-20°C to 70°C		
Humidity	0°C to 30°C	≤95% rel. humidity		
	30°C to 40°C	≤75% rel. humidity		
Altitude	Operating height			
Dimensions (W × H × D)				
364 mm × 112 mm × 420 mm(14.33 in × 4.41 in × 16.54 in)				
Weight				
With IQ-DSG3000 option	6.4kg(14.1lb)			
	6.7kg(14.8lb)			

► Ordering Information

	Description	Order Number
Model	Signal Generator, 9kHz to 3GHz	DSG3030
	Signal Generator, 9kHz to 6GHz	DSG3060
Standard accessories	Quick Guide (Hard Copy)	-
	CDROM (User Guide, Programming Guide)	-
	Power Cable	-
Options	DSG IQ function PC Software	Ultra IQ Station
	Pulse Train Generator	PUG-DSG3000
	High Stable OCXO Reference Clock	OCXO-A08
	I/Q Modulation, Baseband Output	IQ-DSG3000
	Power Meter Controller	PMC-DSG3000
	Rack Mount Kit	RM-DSG3000

NOTE: All instruments, accessories and options can be ordered from your local RIGOL distributors.

Warranty

Three –year warranty, excluding probes and accessories.



Headquarter
RIGOL TECHNOLOGIES, INC.
No.156,Cai He Village,
Sha He Town,
Chang Ping District, Beijing,
102206 P.R.China
Tel:+86-10-80706688
Fax:+86-10-80705070
Email: info@rigol.com

USA
RIGOL TECHNOLOGIES
USA,INC.
7401 First Place,Suite N
Oakwood Village
OH 44146,USA
Tel/Fax: 440-232-4488
Toll free: 877-4-RIGOL-1
Email: info@rigol.com

Europe
RIGOL TECHNOLOGIES EU,
GmbH
Lindbergh str. 4
82178 Puchheim, Germany
Tel: +49(0)89-8941895-0
Email: info-europe@
rigoltech.com



RIGOL® is the registered trademark of RIGOL Technologies, Inc. Product information in this document subject to update without notice. For the latest information about RIGOL's products, applications and services, please contact local RIGOL office or access RIGOL official website:

www.rigol.com

September,2013